

RGT-1201

Product Description

Conventional anti-jamming needle detector



Product description:

Using integrated circuit alarm system, the conventional type needle detector, accord with international standard sensitivity, stability and reliability. Display the exact breakage at eight parts, convenient and quick find the breakage. Sensitivity of 0 ~ 10 stepless adjustment, the NCM number recorder. No-load running for a few minutes, the machine will automatically stop, namely save electricity and to ensure the safety of the electricity. Select automatic operation system, a continuous working segments need to start the machine once, then into automatic operation, can prolong the service life of the start switch for 5 years. More durable than aluminum alloy shell with plastic shell, the biggest advantage is can play signal shielding, improve the stability of the machine. Arc streamline design, luxury and beauty, general configuration.

Application:

A little small and lower requirements for garments, textiles, quilt, knitwear, the application of plush toys and other industries.

Technical parameter:

RGT-1201

| Inspection width | Inspection height | Inspection standard | Speed | Weight | Power/ | Volume |
|------------------|-------------------|------------------------|---------------|--------|--------|-------------|
| 600mm | 100mm | Fe \geq ϕ 1.0mm | 1580*980*890 | 200kg | 60W | AC220V/50HZ |
| 600mm | 150mm | Fe \geq ϕ 1.2mm | 1580*980*930 | | | |
| 600mm | 200mm | Fe \geq ϕ 1.5mm | 1580*980*960 | | | |
| 600mm | 240mm | Fe \geq ϕ 2.0mm | 1580*980*1000 | | | |
| 600mm | 280mm | Fe \geq ϕ 2.5mm | 1580*980*1040 | | | |
| 600mm | 320mm | Fe \geq ϕ 3.0mm | 1580*980*1080 | | | |

| Inspection width | Inspection height | Inspection standard | /mm Volume | Approx weight | Power | Voltage |
|------------------|-------------------|------------------------|----------------|---------------|-------|-------------|
| 800mm | 100mm | Fe \geq ϕ 1.0mm | 1830*1180*890 | 250kg | 60W | AC220V/50HZ |
| 800mm | 150mm | Fe \geq ϕ 1.2mm | 1830*1180*930 | | | |
| 800mm | 200mm | Fe \geq ϕ 1.5mm | 1830*1180*960 | | | |
| 800mm | 240mm | Fe \geq ϕ 2.0mm | 1830*1180*1000 | | | |
| 800mm | 280mm | Fe \geq ϕ 2.5mm | 1830*1180*1040 | | | |
| 800mm | 320mm | Fe \geq ϕ 3.0mm | 1830*1180*1080 | | | |

P.S. The inspection width and height can be customized.