

RGT-1202

Product Description

Enhanced anti-interference needle detector

CE



Product description:

Infrared photoelectric memory data, the accurate rate of 100%, the statistics were seized on the number of qualified environmental detection, convenient for machine installation in an appropriate location.

Frequency display breakage metal foreign bodies in the large and small, eight parts display lamp right breakage metal foreign body parts, convenient and quick find the breakage.

Select automatic operation system, a continuous working segments need to start the machine once, then into automatic operation, can prolong the service life of the operation button for 10 years.

Application:

Be applicable to detect broken needles, tacks, ferrous, iron foreign bodies in textiles, garments, shoes, underwear, zippers, socks, beddings, toys, foods etc.

Technical parameter:

RGT-1202

Inspection width	Inspection height	Inspection standard	Volume/mm	Approx weight	Power	Voltage
400mm	120mm	$Fe \geq \phi 0.8\text{mm}$	1580*980*890	180kg	60W	AC220V/50HZ
	160mm	$Fe \geq \phi 1.0\text{mm}$	1580*980*930			
	190mm	$Fe \geq \phi 1.2\text{mm}$	1580*980*960			
	230mm	$Fe \geq \phi 1.5\text{mm}$	1580*980*1000			

Inspection width	Inspection height	Inspection standard	Volume/mm	Approx weight	Power	Voltage
600mm	120mm	$Fe \geq \phi 0.8\text{mm}$	1580*980*890	180kg	60W	AC220V/50HZ
	160mm	$Fe \geq \phi 1.0\text{mm}$	1580*980*930			
	190mm	$Fe \geq \phi 1.2\text{mm}$	1580*980*960			
	230mm	$Fe \geq \phi 1.5\text{mm}$	1580*980*1000			

P.S. The inspection width and height can be customized.